

Tipology / Tipologia

GROUND RECESSED
WALL RECESSED
CEILING RECESSED
WALL MOUNTED
INCASSI A TERRENO
INCASSI PARETE
INCASSI SOFFITTO
PARETE

The walkable line which interprets space and volume. Ice expresses great effect LED homogeneous linear light. A range of four crystal perimeter-finished elements, aggregable linear fixtures complete with housings that can be loop-powered in only 5 seconds while maintaining the IP67 protection, with a thickness of only 55mm and a width of 30mm. Simple and easy mounting, with a wide range of accessories, floor and surface installation, make it a reference point for the market. *Il segno lineare calpestabile che interpreta lo spazio ed il volume. Ice esprime luce lineare a led omogenea e di grande effetto. Una gamma di quattro elementi con finitura cristallo perimetrale, lineari aggregabili che completi di gusci contenitori permettono di alimentare in loop in soli 5 secondi mantenendo l'IP67, in soli 55mm di spessore e 30mm di larghezza. Di semplice e veloce installabilità, ampia gamma di accessori, utilizzo a pavimento parete e soffitto ne fanno un riferimento per il mercato di competenza.*

ENVIRONMENTS
CONTESTI

Façades and architectural works, wellness, hallway, industrial areas
Facciate e architetture, wellness, spazi d'accesso, industria

Characteristics Caratteristiche

CONSTRUCTION
COSTRUZIONE

Built from corrosion resistant anodised extruded aluminium and cast aluminium, polyester powder coated following several treatments. 10 millimetre thick tempered glass sealed with MS crystalline adhesive with mechanical and thermal shock resistant, IP67 loop connection with quick connector and dedicated cables. Lighting fixture secured onto mounting accessories via slots and retaining clips. Recessed housing in anodised extruded aluminium and wall-mounted casings in coated extruded aluminium fitted with steel cable to prevent falling. Wall mounting brackets in coated AISI 316 stainless steel. Screws and bolts in AISI 304 stainless steel. Power supply voltage of lighting fixtures: 19-24V-DC PWM. *Costruzione in alluminio estruso anodizzato e alluminio pressofuso resistenti alla corrosione, verniciatura a polveri poliesteri previo pluri trattamento. Vetro di sicurezza temprato spessore 10 millimetri sigillato con collante MS cristallino resistente all'urto meccanico e allo sbalzo termico, connessione in loop IP67 ad innesto rapido con connettore e cavi appositi. Fissaggio del corpo illuminante negli accessori di montaggio ad incastro con molle di ritegno. Cassaforme ad incasso in alluminio estruso anodizzato e involucri a parete in alluminio estruso verniciato predisposti con cavo anticaduta in acciaio. Staffe di fissaggio a muro in acciaio inox AISI 316 verniciato. Viteria in inox AISI 304. Tensione di alimentazione dei corpi illuminanti 19-24V-DC PWM.*

OPTICAL SYSTEM
SISTEMA OTTICO

Optical system with PMMA lenses. Tempered safety glass - 10 mm thickness, mechanical and thermal shock resistant. *Sistema ottico a lenti in PMMA. Vetro di sicurezza temprato spessore 10mm - resistente all'urto meccanico e allo sbalzo termico.*

SOURCES / SORGENTI

LED CRI>80 MacAdam 3

LIFETIME


50.000h L80B50 (Ta=25°C)

WIRING
CABLAGGIO ELETTRICO


Remote electrical harness wired for 220-240V 50-60Hz, 24V-DC output (accessories to be ordered separately). Looping facility with IP67 fast connector. Voltage 19-24V-DC PWM. *Cablaggio elettrico con alimentatori remoti a 220-240V 50-60Hz uscita 24V-DC (accessori da ordinare separatamente). Predisposto per linea passante con connettore rapido IP67. Tensione 19-24V-DC PWM.*

STANDARDS / NORME
DIRECTIVES / DIRETTIVE


To see page/Vedere pagina 375



ICE
NO frame recessed
Incasso NO frame




ICE
Frame recessed
Incasso frame




ICE
Plastboard recessed
Incasso cartongesso



ICE
Wall installation
Parete sporgente



ICE
Adjustable wall
*Orientabile a parete
70mm*



ICE
Adjustable wall
*Orientabile a parete
250mm*

ICE D64

CEILING RECESSED
INCASSI SOFFITTO

WALL RECESSED
INCASSI PARETE

GROUND RECESSED
INCASSI A TERRENO


WALL MOUNTED
PARETE

Luminaires
Corpi illuminanti

Masonry
and concrete recessed
Incasso muratura o cemento

Plasterboard recessed
Incasso cartongesso

Wall mounted
Parete




Ice OV

Ice FE

Trimless recessed
Incasso NO FRAME




Recessed with frame
Incasso frame



Fixed
Fisso



Adjusting
Orientabile



Ice FE



Ice OV

