


# SL713AB FL LED



- GR-RAL9006 / Grey RAL9006 / Textured
- WH-RAL9016 / White RAL9016 / Textured

## Optic



MICROPRISMATIC COVER

- Surface mounted quadratic LED luminaire for indoors, comprising :
  - Aluminium profile lightframe, steel sheet canopy, painted
  - Microprismatic diffuser for efficient light diffusion, glare reduction and a high uniformity
  - Predominantly direct light distribution
  - LED Sidelight Technology for a homogenous light distribution over the entire area of the cover
  - Colour rendering index Ra > 80
  - Colour tolerance according to MacAdam ≤ 3 SDCM
  - Also dimmable via TouchDIM®
  - Complete with electric converter
  - VDU application suitable acc. to EN 12464-1
  - 3000 K colour temperature version on demand
  - Special colour versions available upon request

## SL713AB FL LED MICROPRISMATIC COVER 390

IK05 0.7J xx3 - 650°


LAMPHOLDER	WATTAGE	CLASS	CRI	KELVIN	COS Ø ≥ 0,9	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER	EURO
------------	---------	-------	-----	--------	-------------	-------	------------	--------------------------	------------------------	---	---	----------	-------------	-------------	------

### Power LED - dimmable DALI - 220-240 V / 50-60 Hz

LED	21 W	I	80	4000	•	S/C	2 x 48°	3650 lm	2160 lm	80	10	50000 h	●	<b>8713661256430</b>	
LED	21 W	I	80	4000	•	S/C	2 x 48°	3650 lm	2160 lm	80	10	50000 h	○	<b>8713661256410</b>	

### Power LED - 220/240 V 50/60 Hz

LED	21 W	I	80	4000	•	S/C	2 x 48°	3650 lm	2160 lm	80	10	50000 h	●	<b>8713661253430</b>	
LED	21 W	I	80	4000	•	S/C	2 x 48°	3650 lm	2160 lm	80	10	50000 h	○	<b>8713661253410</b>	



## SL713AB FL LED MICROPRISMATIC COVER 615

IK05 0.7J xx3 - 650°

LAMPHOLDER	WATTAGE	CLASS	CRI	KELVIN	COS Ø ≥ 0,9	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER	EURO
------------	---------	-------	-----	--------	-------------	-------	------------	--------------------------	------------------------	---	---	----------	-------------	-------------	------

### Power LED - dimmable DALI - 220-240 V / 50-60 Hz

LED	46 W	I	80	4000	•	S/C	2 x 48°	6090 lm	4740 lm	80	10	50000 h	●	<b>8713661506430</b>	
LED	46 W	I	80	4000	•	S/C	2 x 48°	6090 lm	4740 lm	80	10	50000 h	○	<b>8713661506410</b>	

### Power LED - 220/240 V 50/60 Hz

LED	46 W	I	80	4000	•	S/C	2 x 48°	6090 lm	4740 lm	80	10	50000 h	●	<b>8713661503430</b>	
LED	46 W	I	80	4000	•	S/C	2 x 48°	6090 lm	4740 lm	80	10	50000 h	○	<b>8713661503410</b>	

