




17 Maximus Duo LED Picture light

When lighting large paintings with strong frames, a large picture light is required for optical balance between the image and the light. Introducing "Maximus", which can be adjusted to fit pictures with widths of several meters.

An additional feature of using the "Maximus" for lighting paintings in museums is that it produces ambient lighting. Most of the light is directed towards the painting, however, some unavoidable stray light fills the room with an unnoticeable background brightness, which is good for our wellbeing.

Package contents: Light complete with LED bulbs, fastening set and dimmable ballast. (Sample on/off switch as well as a 100% touch control continuous dimmer.)

Technical specifications: **IP20**  

Material:	Brass
Illuminant:	Duo LED
Illuminant lifespan:	max. 50000 hours
LED efficiency class:	
Voltage:	24V
Light tube:	Ø 34 mm, rotatably
Arm tube:	Ø 8 mm
Dimmable ballast 12W:	94 x 36 x 18 mm
Dimmable ballast 30W:	133 x 46 x 24 mm
Light could be coupled.	

Length	Colour	Watt / Lumen	Item number
490 mm	Brass	8 Watt, 552 lm	17M 005 DL20
650 mm	Brass	11 Watt, 759 lm	17M 006 DL20
770 mm	Brass	13 Watt, 897 lm	17M 007 DL20
950 mm	Brass	17 Watt, 1174 lm	17M 009 DL20
1250 mm	Brass	23 Watt, 1588 lm	17M 012 DL20
1550 mm	Brass	29 Watt, 2002 lm	17M 015 DL20





Surface colour Item number

Brass		17 MO 05DL20
Chrome		17 CO 05DL20
Nickel		17 NO 05DL20
Nickel-mat	Not at 1550 mm	17 XO 05DL20
Bronze		17 BO 05DL20
Brass-mat		17 TO 05DL20
Black		17 SO 05DL20
White		17 WO 05DL20
Gold 24ct		17 GO 05DL20
Gold-mat 24ct	Not at 1550 mm	17 YO 05DL20

LED Light colour & Replacement bulbs



3000 K	Neutralwhite RA:94	67DL 05NW 24
2400 K	Warmwhite RA:80	67DL 05WW 24

Ballast

LED EVG 12W 90VD24LD12



LED EVG 30W 90VD24LD29



Arm type Item number

Type 20 Standard	17MO05DL 20
Type 25	17MO05DL 25
Type 30	17MO05DL 30
Type 10	17MO05DL 10

Touch-Dimmer 67TD08LD24




Diffuser cover 67MA01PM00




Type 20
200 mm



Type 25
250 mm



Type 30
300 mm



Type 10
100 mm



Coupling arm
Depends on arm type

